



## Leak Sealer

1 Litre treats up to 60,000 litres of water



### What is it?

Lo-Chlor Leak Sealer seals leaks in swimming pools and spas.

### Who needs it?

- Any pool or spa owner who has a minor leak in their pool or spa.

### What does it do?

- Seals minor leaks in concrete and fibreglass swimming pools and spas.

### What advantages does it have over other similar products?

- Very easy and economical to use.

### Professional tips:

- Before use remove filter grids and cartridges.
- Alternatively select "by-pass" or "re-circulate" settings if available.
- For best results add leak sealer through the skimmer basket when the pump is turned off. This allows the product to flow slowly through the pipe work and allows for a quick seal in this area.
- Wait 30 minutes and then turn the pump on.
- Pump should be left running for at least 8 hours.
- Where possible attach a pool vacuum hose with vacuum head at the deepest point on the pool.
- This will assist the leak sealing process. Leak Sealer is much heavier than water and it "sinks" to the deepest point. By positioning the vacuum head in this area it ensures maximum utilisation of the product.
- Vacuum any residue in the pool to waste.
- Replace the filter grids or cartridges after 24 hours and resume normal operation.
- This product should not be used when the rate of water loss exceeds 1 inch in a 60,000 litres pool.
- Minor leaks may benefit from a second application where the leak appears to have slowed but not sealed completely from the initial application.